

REFERENCES

- Alireza, A. (2008). Wood-plastic composites as promising green-composites for automotive industries. *Bioresource Technology*, 4661-6667.
- Anatole, A. (2007). *Wood Plastic Composites*. Hoboken, New Jersey: John Wiley & Sons, Inc.
- Bezhad, K. & Seyed, M.H.K. (2011). Effect of nanoclay dispersion on physical and mechanical properties of wood flour/polypropylene/glass fiber hybrid composites. *Hybrid Nanocomposites*, 1741-1751.
- Gong, G.N., Nystrom, B., & Joffe, R. (2013). Development of polyrthylene/nanoclay masterbatch for use in wood-plastic composites. *Plastic, Rubber and Composites*, 167-175.
- Han, G., Lei, Y., Wu, Q., Kojima, Y., & Suzuki, S. (2008). Bamboo-Fiber Filled High Density Polyethylene Composites: Effect of Coupling Treatment and Nanoclay. *J Polymer Environment*, 123-130.
- Hua, G., Yanjun, X., Rongxian, O., & Qingwen, W. (2012). Grafting effects of polypropylene/polyethylene blends with maleic anhydride on the properties of the resulting wood-plastic composites. *Composites:Part A*, 150-157.
- Kin, T.L, Chong, G., & David, H. (2006). A critical review on nanotube and nanotube/nanoclay related polymer composite materials. *Composite Part B: Engineering*, 425-436.
- Kristiina, O.N., & Mohini, S. (2008). *Wood-polymer composite*. Cambridge England: Woodhead Publishing Limited.
- Mahjoub, R., Yatim, J.M., Mohd Sam, A.R., & Hashemi, S.H. (2014). Tensile properties of kenaf fiber due to various conditions of chemical fiber surface modifications. *Construction and Building Materials*, 103-113.
- Meysam, Z., Taghi, T., Alireza, A., Mehrab, M., & Alireza, S. (2013). A Comparative Study on Some Properties of Wood Plastic Composites Using Canola Stalk, Paulownia, and Nanoclay. *Applied Polymer Science*, 877-833.
- Mohd Rosnan, R., & Arsad, A. (2013). Effect of MMT concentrations as reinforcement on the properties of recycled PET/HDPE nanocomposites. *J Polymer Eng*, 615-623.
- Nourbakhsh, A., & Ashori, A. (2009). Preparation and Properties of Wood Plastic Composites Made of Recycled High-density Polyethylene. *Composite Materials*, 877-883.
- Olewnik, E., Garman, K., & Czerwinski, W. (2010). Thermal properties of new composites based on nanoclay, polyethylene & polypropylene. *J Therm Anal Calorim*, 323-329.
- Onuegbu, G.C., & Iqwe, I.O. (2011). The Effects of Filler Contents and Particle Sizes on the Mechanical and End-Use Properties of Snail Powder Filled Polypropylene. *Material Sciences and Application*. 2, 811-817.

- Saba, N., Paridah, M.T., & Jawaid, M. (2015). Mechanical properties of kenaf fiber reinforced polymer composite: A review. *Construction and Building Materials*, 87-96.
- Scott, G. (1999). Polymer and the environment. *Cambridge: RSC Paperbacks*, 132.
- Sellers, T.Jr., Miller, G.D.Jr., & Katabian, M. (2000). Recycled thermoplastics reinforced with renewable lignocellulosic materials. *Forest Product Journal*, 50, 24-28.
- Shao, Y.L., Tsu, H.Y., Sheng, F.L., & Te, H.Y. (2012). Optimized material composition to improve the physical and mechanical properties of extruder wood-plastic composites (WPCs). *Construction and Building Materials*, 120-127.
- Summit, M.Y., & Kamal, Y. (2015). Mechanical and physical properties of wood-plastic composites made of polypropylene, wood flour and nanoclay. *Proceeding-Kuala Lumpur International Agriculture, Forestry and Plantation*, 967-978.
- Thanate, R., Natchayapa, T., & Chtree, H. (2012). Mechanical and thermal properties of oil palm wood. *ScienceAsia*, 289-294.
- Wang, Y., & Gao, J. (2006). Argawal US. *Compos. Part B-Eng*, 6, 399-407.
- Yam, K.L., Gogai, B.K., Lai, C.C., & Selke, S.E. (1990). Composites from compounding wood fibers with recycled high-density polyethylene. *Polymer Engineering Science*, 30(11), 9-693.
- Yihua, C., Stephen, L., Bahman, N., Moe, C., & Jie, T. (2008). Fabrication and interfacial modification of wood/recycled plastic composite materials. *Composite Part A: Applied Science and Manufacturing*, 39, 655-661.